

NAME

putc – buffered output

SYNOPSIS

```
mov    $filename,r0
jsr    r5,fcreat; iobuf
```

```
fcreat(file, iobuf)
char *file;
struct buf *iobuf;
```

(get byte in r0)

```
jsr    r5,putc; iobuf
```

```
putc(c, iobuf)
```

```
int c;
```

```
struct buf *iobuf;
```

(get word in r0)

```
jsr    r5,putw; iobuf
```

[putw not available from C]

```
jsr    r5,flush; iobuf
```

```
fflush(iobuf)
```

```
struct buf *iobuf;
```

DESCRIPTION

Fcreat creates the given file (mode 666) and sets up the buffer *iobuf* (size 518 bytes); *putc* and *putw* write a byte or word respectively onto the file; *flush* forces the contents of the buffer to be written, but does not close the file. The format of the buffer is:

```
iobuf:  .+.2          / file descriptor
        .+.2          / characters unused in buffer
        .+.2          / ptr to next free character
        .+.512. / buffer
```

Or in C,

```
struct buf {
    int fildes;
    int nunused;
    char *nxtfree;
    char buff[512];
};
```

Fcreat sets the error bit (c-bit) if the file creation failed (from C, returns -1); none of the other routines returns error information.

Before terminating, a program should call *flush* to force out the last of the output (*fflush* from C).

The user must supply *iobuf*, which should begin on a word boundary.

To write a new file using the same buffer, it suffices to call *[f]flush*, close the file, and call *fcreat* again.

SEE ALSO

creat(II), write(II), getc(III)

DIAGNOSTICS

error bit possible on *fcreat* call.

BUGS