CREF(I) 2/5/73 CREF(I)

NAME

cref - make cross reference listing

### SYNOPSIS

cref [ -acilostux123 ] name ...

#### DESCRIPTION

*Cref* makes a cross reference listing of program files in assembler or C format. The files named as arguments in the command line are searched for symbols in the appropriate syntax.

The output report is in four columns:

(1) (2) (3) (4) symbol file see text as it appears in file below

Cref uses either an *ignore* file or an *only* file. If the  $-\mathbf{i}$  option is given, it will take the next available argument to be an *ignore* file name; if the  $-\mathbf{o}$  option is given, the next available argument will be taken as an *only* file name. *Ignore* and *only* files should be lists of symbols separated by new lines. If an *ignore* file is given, all the symbols in that file will be ignored in columns (1) and (3) of the output. If an *only* file is given, only symbols appearing in that file will appear in column (1). Only one of the options  $-\mathbf{i}$  or  $-\mathbf{o}$  may be used. The default setting is  $-\mathbf{i}$ . Assembler predefined symbols or C keywords are ignored.

The -s option causes current symbols to be put in column 3. In the assembler, the current symbol is the most recent name symbol; in C, the current function name. The -l option causes the line number within the file to be put in column 3.

The -t option causes the next available argument to be used as the name of the intermediate temporary file (instead of /tmp/crt??). The file is created and is not removed at the end of the process.

# Options:

- a assembler format (default)
- c C format input
- i use *ignore* file (see above)
- 1 put line number in col. 3 (instead of current symbol)
- **o** use *only* file (see above)
- s current symbol in col. 3 (default)
- t user supplied temoprary file
- u print only symbols that occur exactly once
- x print only C external symbols
- 1 sort output on column 1 (default)
- 2 sort output on column 2
- 3 sort output on column 3

# FILES

/tmp/crt?? temporaries

/usr/lib/aign default assembler ignore file

/usr/lib/cign default C *ignore* file /usr/bin/crpost post processor

/usr/bin/upost post processor for **–u** option

/bin/sort used to sort temporaries

#### SEE ALSO

as(I), cc(I)

**BUGS**