

NAME

tss – interface to MH-TSS

SYNOPSIS

tss

DESCRIPTION

Tss will call the Honeywell 6070 on the 201 data phone. It will then go into direct access with MH-TSS. Output generated by MH-TSS is typed on the standard output and input requested by MH-TSS is read from the standard input with UNIX typing conventions.

An interrupt signal is transmitted as a ‘break’ to MH-TSS.

Input lines beginning with ‘!’ are interpreted as UNIX commands. Input lines beginning with ‘~’ are interpreted as commands to the interface routine.

~<file	insert input from named UNIX file
~>file	deliver tss output to named UNIX file
~p	pop the output file
~q	disconnect from tss (quit)
~r file	receive from HIS routine csr/daccopy
~s file	send file to HIS routine csr/daccopy

Ascii files may be most efficiently transmitted using the HIS routine *csr/daccopy* in this fashion. Bold face text comes from MH-TSS. *Aftname* is the 6070 file to be dealt with; *file* is the UNIX file.

SYSTEM? *csr/daccopy (s) aftname*

Send Encoded File *~s file*

SYSTEM? *csr/daccopy (r) aftname*

Receive Encoded File *~r file*

FILES

/dev/dn0, /dev/dp0, /etc/msh

DIAGNOSTICS

Most often, ‘Transmission error on last message.’

BUGS

When problems occur, and they often do, *tss* exits rather abruptly.