

NAME

`opr` – off line print

SYNOPSIS

`opr` [`-destination`] [`-crm`] [`name ...`]

DESCRIPTION

Opr causes the named files to be printed off line at the specified destination. If no names appear the standard input is assumed.

At the mother system the following destinations are recognized. The default destination is **mh**.

lp Local line printer.

mh GCOS at Murray Hill Comp Center. GCOS identification must be registered in the UNIX password file (see `passwd` (V)).

sp Spider network printer.

xx The two-character code *xx* is taken to be a Murray Hill GCOS station id. Useful codes are 'r1' for quality print and 'q1' for quality print with special ribbon.

Opr uses spooling daemons that do the job when facilities become available. Flag `-r` causes the named files to be removed when spooled. Flag `-c` causes copies to be made so as to insulate the daemons from any intervening changes to the files.

Flag `-m` causes mail to be sent when UNIX is finished transmitting the file. For GCOS jobs the mail includes the `snumb`.

FILES

<code>/etc/passwd</code>	personal ident cards
<code>/lib/dpr</code>	dataphone spooler
<code>/etc/dpd</code>	dataphone daemon
<code>/usr/dpd/*</code>	spool area
<code>/lib/lpr</code>	line printer spooler
<code>/etc/lpd</code>	line printer daemon
<code>/usr/lpd/*</code>	spool area
<code>/lib/npr</code>	spider network spooler

SEE ALSO

`fsend` (I), `dpd` (VIII), `lpd` (VIII)

BUGS

Line printer spooler doesn't handle flags.
Spider network spooler doesn't spool.